


XP-G480E

Industrial Thermal Transfer Label Printer

Xprinter®

XP-G480E

Industrial Thermal Transfer Label Printer



- Label printer for industrial machine
- Network interface, flexible operation, large capacity, visual window

Printer Specifications

Resolution	300 DPI
Print Method	Thermal Transfer / Direct Thermal
Memory	128 MB RAM / 128 MB Flash
Max. Print Width	4.09 in./104 mm
Max. Print Speed	Up to 8 ips (203 mm/s)
Media Sensors	Movable Black Mark Sensor / Movable Gap Sensor
Emulation	TSPL, ZPL, EPL, DPL
Interface	USB+Serial+Lan, USB+Serial+Lan+Parallel+GPIO (Optional Wireless Connectivity: Bluetooth / Wi-Fi)
Display Screen	3.5" LCD, 320*480 pixel
Others	Standard RTC, Standard SD Card Slot

Media and Ribbon Characteristics

Media Length	0.39 in. ~ 35 in. (10 mm ~ 889 mm)
Media Width	0.78 in. ~ 4.7 in. (20 mm ~ 120 mm)
Media Roll Size	8 in./203 mm Outer Diameter, Core Inner Diameter: 1 in. (25.4 mm)
Thickness	0.0023 in. (0.06 mm) Min.; 0.01 in. (0.254 mm) Max.
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media
Ribbon Outside Diameter	3.58 in. / 91 mm
Max. Ribbon Length	600 Meters (1968 ft.)
Ribbon Width	0.78 in. ~ 4.3 in. (20 mm ~ 110 mm)
Ribbon Core I.D.	1 in. / 25.4 mm

Environment Condition

Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Fonts/Graphics/Symbologies

1D Bar Codes	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5), digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D Bar Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Fonts and Graphics	Font 0 ~ Font 8

Software

Driver	Windows / Linux / Mac / Android / Chrome OS
SDK	Windows / Linux / Android / iOS
Software	Bartender UltraLite / Mobile Label Design App

Accessories

Standard Accessories	Power Cord, USB Cable, User Manual, CD, Ribbon Spindle*2, Ribbon For Test, Ribbon Paper Core, Label Roll For Test
Factory Installed Options	Bluetooth Module, Wi-Fi Module, Peel-off Module, Cutter Module
User Options	8" External Paper Roll Holder

Physical Characteristics

Dimension	504 mm × 257 mm × 297 mm (D × W × H)
Weight	11 Kg



300DPI
203mm/s


- Visual operation interface



- Visual perspective window



- Ribbon capacity 600M long



- 128MB Flash Memory/
128MB SDRAM



1. Plastic frame
2. Transparent cover design
3. Menu
4. Ribbon roller
5. Label roller
6. Print head

Distributor in Morocco:

PROMATECH

GSM :00212 6 66 92 81 79 /68



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 393 2978
Http://www.xprintertech.com
Email: overseas@xprinter.net

